

Abocoat 8006-3™

All Purpose, Clear Epoxy Coating



Applications:

Abocoat 8006-3 provides heavy-duty protection on concrete, wood, and metal surfaces, preventing corrosion and wear. High gloss. Great versatility, superior adhesion, flexibility, hardness, and water, salt and chemical resistance. Inhibits rust. It is frequently specified for laboratories, commercial kitchens, hospitals, and industrial flooring. Add sand or ColorGrit™ to add slip-resistance.

Features and Benefits:

- Solvent-based epoxy coating with superior adhesion
- High impact resistance
- High abrasion resistance
- High resistance to water, chemicals and salts
- High gloss
- Easy to apply

Packaging:

- 2 Quart Kit
- 2 Gallon Kit
- 10 Gallon Kit

Manufactured By:



Technical Characteristics:

- Weight/gallon: Part A - 8.5 lbs / 3.86 Kg
Part B - 8.8 lbs / 3.99 Kg
- Viscosity (Approx): 225 cps
- Pull-off Strength (ASTM D4541): 458 psi
- Abrasive Resistance (ASTM D4060): 0.085g (CS 17 / Load 1000 / Cycles 1000)
- Coefficient of Friction (ASTM D1894): 2.75
- Pencil Hardness: 3B
- Chemical Resistance (ASTM D543): High
- Impact Resistance (ASTM D4226): 85.0
- Heat Resistance (ASTM D2485): 212°F (100°C)
- Pot Life: 60-75 Hours
- Hardening Time (Approx.): 3 Hours
- VOC EPA Method #24: 190g/L
- Primer: None
- % Solids by Weight: 44%
- Coverage per Gal. (Approx.): 250 sq. ft. x 3 mil
- Shelf Life: 2 years

**The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

Instructions:

- This is a two part product: A (resin) and B (converter).
- Mix Parts A and B in the ratio specified on the labels. Wait 45 minutes before applying.
- Apply mixture to clean, dry, surface.
- Apply with spraygun, brush or roller.
- Recoat within 1 to 2 days if desired.
- Refer to detailed instructions accompanying product.

LIMITED WARRANTY

As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.

5501-95th Avenue
Kenosha, Wisconsin 53144 USA
1-800-445-1754
www.abatron.com

ISO 9001 Registered. Made in USA.