

SS-Bond P™

Stainless Steel-filled Structural Adhesive Putty



Applications:

Epoxy compound for the permanent repair, maintenance, bonding, and filling of metal and other rigid surfaces. Use where a filler is needed that is as heavy, hard, and wear-resistant as iron, as well as rust-proof and more chemical resistant. Repair of stainless steel equipment.

Features and Benefits:

- High-impact, wear-resistant 2 component putty
- Bonds permanently to metal, ceramics, glass, wood, and most rigid surfaces
- Dimensionally stable and shrink-free
- Unaffected by atmospheric conditions, salt and fresh water, alkalis, diluted acids, oils, greases, and many solvents
- Can be machined, drilled, tapped, and painted
- Can be applied in any thickness
- Ample working time
- Room-temperature cure
- Reduce down-time and get equipment back into service quickly

Manufactured By:



Technical Characteristics:

- Weight/gallon: 21.5; Kg/L: 2.5
- Pot life: 1 hour at 75°
- Hardening time: 2-3 hours at 75°F
- Color: Gray
- 100% Solids
- Flash Point: A >450°F; B >245°F
- Hardness Shore D: 80
- Tensile Strength (7 Days): 2,844 psi
- Flexural Strength (7 Days): 6,678 psi
- Compressive Strength (7 Days): 8,654 psi
- Elongation (7 Days): 4.3%
- Shear Test (7 Days): 2,487

**The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

Instructions:

- This is a two part product: A (resin) and B (hardner).
- Mix Parts A and B in the ratio specified on the labels.
- Apply mixture to clean, dry, surface free of contaminants, oil, grease, wax, and debris, with putty knife or mixing blade.
- Let mixture harden. When hard, application is complete.

Packaging:

- 1 Lb. Kit
- 4 Lb. Kit

LIMITED WARRANTY

As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.

WARNING! IRRITANT.
KEEP OUT OF REACH OF CHILDREN.
Read statement on container before using.

5501-95th Avenue
Kenosha, Wisconsin 53144 USA
1-800-445-1754
www.abatron.com

ISO 9001/2015 Registered. Made in USA.