

BestBond® Crack Repair

High-Strength Epoxy Crack Repair Compound



Applications:

BestBond® Crack Repair is a high-strength epoxy crack repair compound that permanently fills and repairs cracks in concrete, stone, masonry, and most rigid surfaces. Its added flexibility resists cracking due to seasonal temperature changes. It is recommended for horizontal applications. Each 9 fl. oz. cartridge fills 16 cubic inches. For exterior or interior applications.

Features and Benefits:

- Permanently fills and repairs cracks
- Shrink-free: contains no water or solvents
- Effective on concrete, stone, masonry, and most rigid surfaces
- Very low odor
- UV Resistant



Manufactured By:



Technical Characteristics:

- Weight/gallon: 10.1 lbs / 4.59 Kg
- Color: Light Gray
- Application Temperature: 50-95°F (10-35°C)
- Pot Life: 48 minutes at 77°F (25°C)
- Hardening Time: Approximately 60 minutes at 77°F (25°C)
- Flame Resistance (ASTM D3801-96e1): Yes
- Viscosity (cps; ASTM D562): 19,000
- Tensile Strength (ASTM D638): 930 psi
- Elongation (ASTM D638): 97%
- Flexural Strength (ASTM D790): 620 psi
- Compressive Strength (ASTM D695): 5,800 psi
- Hardness - Shore A (D): 90 (59)
- Solids by Weight: 100%
- VOC (EPA method #24): 0%

**The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

Instructions:

The 9-fluid ounce cartridge of BestBond Crack Repair can be applied with a caulking gun. Larger volumes may be applied with a squeegee or trowel. Refer to detailed instructions accompanying product for full description.

Packaging:

- 9 Fl. Oz. Cartridge
- 3 Gallon Kit
- 15 Gallon Kit

LIMITED WARRANTY

As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.

5501-95th Avenue
Kenosha, Wisconsin 53144 USA
1-800-445-1754
www.abatron.com

ISO 9001 Registered. Made in USA.