

# BestBond® Joint Sealant

## High-Strength Epoxy Joint Sealant Compound



### Applications:

BestBond® Joint Sealant is a high-strength epoxy joint sealant that fills joints and cracks in concrete and most rigid surfaces. Its higher elongation allows for movement and settling of the concrete. Recommended for horizontal applications. Each 9 fl. oz. cartridge fills 16 cubic inches. For exterior or interior applications.

### Features and Benefits:

- Tenacious, high-strength bond
- Bonds to virtually any rigid surface
- Permanent adhesion
- Shrink-free
- Chemical, abrasion and UV resistant
- Virtually no VOCs
- Fast hardening



Manufactured By:

 **ABATRON**

### Technical Characteristics:

- Weight/gallon: 8.5 lbs / 3.86 Kg
- Color: Gray
- Application Temperature: 50-95°F (10-35°C)
- Pot Life: 45 minutes at 77°F (25°C)
- Hardening Time: Approximately 35-60 minutes at 77°F (25°C)
- Flame Resistance (ASTM D3801-96e1): Yes
- Viscosity (cps; ASTM D562): 12,000
- Tensile Strength (ASTM D638): 140 psi
- Compressive Strength (ASTM D695): 1,600 psi
- Hardness - Shore A (D): 80 (30)
- Elongation: 60%
- Solids by Weight: 100%
- VOC (EPA method #24): 0%
- Coverage: 231 cu. in. / gal.

*\*The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

### Instructions:

The 9-fluid ounce cartridge of BestBond Joint Sealant can be applied with a caulk gun. Larger volumes may be applied with a squeegee or trowel. Refer to detailed instructions accompanying product for full description.

### Packaging:

- 9 Fl. Oz. Cartridge
- 3 Gallon Kit
- 15 Gallon Kit

#### LIMITED WARRANTY

*As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.*

5501-95<sup>th</sup> Avenue  
Kenosha, Wisconsin 53144 USA  
1-800-445-1754  
www.abatron.com

ISO 9001 Registered. Made in USA.