

Abocast 8005-6™

Bond New Concrete to Old



Applications:

- Creates a stronger-than-concrete bond between wet-poured concrete and old concrete.
- Use this bonding agent to repair bridges, runways, ramps, decks, driveways, and patios.
- Resurface concrete and terrazzo floors with thin, lightweight layers of concrete.
- Acts as binder for aggregates that must bond to wet, underwater, or cold surfaces.

Abocast 8005-6 is easy to apply with a brush or roller. It is outstanding for resurfacing floors, and can be extended with fillers like sand, gravel, or chips. Chemically resistant and unaffected by atmospheric conditions, water, alkalies, diluted acids, several solvents, oils and greases.

Features and Benefits:

- Two part epoxy compound provides high adhesion.
- Acid, alkali and fuel resistant.
- Hardens on wet surfaces and under water.
- Ideal where wet concrete is to be cast onto old concrete or steel and forms a permanent bond.
- Bonds to most rigid surfaces.

Manufactured By:



Technical Characteristics:

- Weight/gallon: Part A - 11.0 lb / 5.0 Kg; Part B - 10 lb / 4.5 Kg
- Pot life: 30 minutes at 77°F / 25° C
- Hardening time: 0.5 - 3 hours at 77°F / 25° C
- Color: Tan
- 100% Solids
- Tensile Strength (psi): 3,061
- Compressive Yield (psi): 13,809
- Elongation %: 11.7

*The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.

Instructions:

- This is a two part product: A (resin) and B (hardner).
- Mix Parts A and B in the ratio specified on the labels.
- Apply mixture to clean, dry, surface free of contaminants, oil, grease, wax, and debris, with brush, roller or squeegee.
- Apply new concrete onto Abocast 8005-6 before the 8005-6 hardens, within about 2 - 5 hours.
- Read instructions accompanying product.

Packaging:

- 1.5 Gallon Kit
- 10 Gallon Kit

LIMITED WARRANTY

As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.

WARNING! IRRITANT.
KEEP OUT OF REACH OF CHILDREN.
Read statements on containers before using.

5501-95th Avenue
Kenosha, Wisconsin 53144 USA
1-800-445-1754
www.abatron.com

ISO 9001/2015 Registered. Made in USA.