

# LiquidWood® Cold

## Epoxy Wood Consolidant

### for Cold Weather Use



#### Applications:

LiquidWood Cold is a variant of the original LiquidWood® wood consolidant, specially formulated for use in colder temperatures\*. It is designed to penetrate and harden wood to restore strength, and impart resistance to water, weather, and wear. Use in window sills, columns, decks, and other wooden architectural elements. Serves as a primer for WoodEpoxy® wood replacement compound. Apply with a brush.

\* LiquidWood Cold is recommended for use in temperatures ranging from 35°F to 60°F (2°C - 16°C).

#### Features and Benefits:

- Deep penetrating wood consolidant for restoring strength
- Permanently reinforces deteriorated wood
- Provides water and weather resistance
- Low odor
- Exceptional adhesion
- Hardened product can be sawed, planed, routed, carved, drilled, nailed, sanded, and painted.
- Easy to apply
- Primer for WoodEpoxy

Manufactured By:



#### Technical Characteristics:

- Weight/gallon: Part A - 9.5 lbs / 4.3 Kg; Part B - 9.3 lbs / 4.2 Kg
- Appearance: Part A: Clear colorless liquid; Part B: Clear, light amber liquid
- % Solids by Weight (ASTM D2369): 89%
- Mix Ratio (A:B): 2:1 (by volume)
- Tensile Strength (ISO 527-1,2): 400 psi
- Elongation (ISO 527-1,2): 101%
- Compressive Strength (ISO 604): 37,700 psi
- Flexural Strength (ISO 178): 100 psi
- Applicator: Brush; applicator bottle
- Application Temperature: 35°F to 60°F (1.7°C - 15.6°C)
- Pot Life: 15 minutes @ 72°F (22°C)
- Hardening Time: Overnight at 35°F (2°C)

*\*The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

#### Instructions:

- Apply to a clean and dry surface that is free of contaminants, oil, grease, wax, old paint and debris.
- Mix 2 parts by volume of LiquidWood Cold Part A with 1 part of LiquidWood Cold Part B.
- Apply mixture with a brush or applicator bottle.
- Refer to detailed instructions accompanying product.

#### Packaging:

- 3 Pint Kit

#### LIMITED WARRANTY

*As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.*

5501-95<sup>th</sup> Avenue  
Kenosha, Wisconsin 53144 USA  
1-800-445-1754  
www.abatron.com

ISO 9001 Registered. Made in USA