

WoodEpox® Cold

Wood Replacement Compound for Cold Weather Use



Applications:

WoodEpox Cold is a variant of the original WoodEpox® wood replacement compound that is specially formulated for use in colder temperatures*. This lightweight, epoxy adhesive putty is designed to repair, replace, extend or fill wood and most rigid surfaces. Use in window sills, columns, decks, and other wooden architectural elements. WoodEpox Cold is shrink-free, and can be used in any thickness. Apply with a putty knife or spatula.

* WoodEpox Cold is recommended for use in temperatures ranging from 35°F to 60°F (2°C - 16°C).

Features and Benefits:

- Shrink-free wood replacement compound
- Bonds permanently
- Use in any thickness
- Hardened product can be painted, stained, wood-grained, sawed, nailed, planed, sanded, carved and machined like wood
- Contains virtually no VOCs or noxious odors
- Light, neutral color can be changed by mixing with pigments
- Easy to apply

Manufactured By:



Technical Characteristics:

- Weight/gallon: Part A - 3.9 lbs / 1.8 Kg; Part B - 3.1 lbs / 1.4 Kg
- Appearance: Light Weight Putty
- % Solids by Weight: 100%
- Mix Ratio (A:B): 1:1 (by volume)
- Tensile Strength (ISO 527-1,2): 800 psi
- Elongation (ISO 527-1,2): 1%
- Compressive Strength (ISO 604): 1,900 psi
- Flexural Strength (ISO 178): 1,900 psi
- Applicator: Putty Knife; Spatula
- Application Temperature: 35°F to 60°F (2°C - 16°C)
- Pot Life: Approx. 25 minutes @ 35°F (2°C)
- Hardening Time: Overnight at 35°F (2°C)

**The above information is based upon laboratory testing. Users are urged to test the product under their own conditions.*

Instructions:

- Thoroughly mix equal volumes of Part A and Part B of WoodEpox Cold.
- Apply WoodEpox Cold to wood primed with LiquidWood® Cold while the LiquidWood Cold is still "tacky" to fill cracks, holes, and replace missing wood.
- Sand, plane, shape, paint and stain restored wood as desired.
- Refer to detailed instructions accompanying product.

Packaging:

- 2 Quart Kit

LIMITED WARRANTY

As uses and applications of this product are beyond the control of the manufacturer, all warranties, including the implied warranties of merchantability and fitness for a particular purpose, are excluded. In the event of manufacturing defects in the product, purchasers' remedies are limited to the replacement of the product or the refund of its purchase price. Liability for consequential damages is expressly excluded.

5501-95th Avenue
Kenosha, Wisconsin 53144 USA
1-800-445-1754
www.abatron.com

ISO 9001 Registered. Made in USA