



ABATRON, INC.

5501 – 95th Ave., Kenosha, WI 53144 U.S.A
(262) 653-2000 Fax (262) 653-2019
www.abatron.com e-mail: info@abatron.com
24 Hour Emergency No: (800) 424-9300

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product Name: LiquidWood B Cold Weather **Product Class:** Modified aliphatic amine
Product Code: LWCBP **Product Type:** Epoxy Curing Agent
Recommended Use: Epoxy resin hardener used to repair and restore damaged or deteriorated wood.
Uses advised against:

Manufacturer/Supplier: Abatron, Inc.
5501 95th Ave., Kenosha WI, 53144
Phone: 262-653-2000
Email: info@abatron.com

Telephone: For 24 Hour Emergency Assistance
Call CHEMTREC (800) 424-9300 (USA)
1-703-527-3887 (International)

SECTION 2: Hazards Identification

Emergency Overview: Danger. Irritant. Clear, amber colored liquid with a slightly irritating ammonia odor. Material is harmful if swallowed. Material causes skin irritation and prolonged contact may lead to sensitization and an allergic skin reaction. Material causes severe eye irritation. Material is harmful if inhaled and can cause severe respiratory tract irritation.

Hazard Pictograms



Signal Word: Danger

Hazard Statements

Causes severe skin burns and eye damage
Toxic in contact with skin
May cause an allergic skin reaction
Toxic if inhaled
Suspected of causing genetic defects
May cause damage to organs (kidney, liver)
May cause respiratory irritation
Toxic if swallowed
May damage fertility. May damage the unborn child

Precautionary Statements

Do not breathe dust/fumes/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

IF eye irritation persists: Get medical advice/attention.

IF ON SKIN: wash with plenty of soap and water.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF SKIN irritation or rash occurs: Get medical advice/attention.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

Avoid release to the environment. Collect spillage.

Dispose of contents/container to be specified in accordance with regulations.

SECTION 3: Composition/Information on Ingredients

Composition: The exact composition is a trade secret. Proprietary liquid amidoamines.

Hazardous Ingredients

Substance Name	CAS Number	Concentration (%)	Hazard Classification
m-phenylenebis(methylamine)	1477-55-0	8 – 64%	Eye Dam. 1 H318 Skin Corr. 1B H314 Skin Sens. 1B H317 Acute Tox. 4 H302 Acute Tox. 4 H332 Aquatic Chronic 3 H412
phenol	108-95-2	1 – 16%	Acute Tox. 3 H301 Acute Tox. 3 H311 Acute Tox. 3 H331 Skin Corr. 1B H314 Muta.2 H341 STOT RE 2 H373
2-ethoxyethyl acetate	111-15-9	10-30%	Flam. Liq. 3 H226 Acute Tox. 4 H302 Acute Tox. 4 H312 Acute Tox. 4 H332 Repro. Tox. 1B H360FD

SECTION 4: First Aid Measures

Eye Contact: Immediately flush eyes with water for at least 15 minutes and check for and remove contacts. Do not delay. Hold eyelids apart to rinse entire eye surface. Seek medical attention if irritation persists. Continue washing if medical attention is not immediately available.

Skin Contact: Wipe off excess immediately and wash affected area with soap and water for at least 15 minutes. Remove contaminated clothing or shoes and seek medical attention if irritation persists. Continue washing if irritation persists. NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.

Inhalation: If inhaled, remove victim to fresh air and consult medical personnel immediately. If person is not breathing or breathing is irregular, provide oxygen with the aid of trained personnel only. If unconscious, place in recovery position and seek medical attention immediately.

Ingestion: Wash out mouth with small amounts of water and remove person to fresh air. Do not induce vomiting unless directed to do so by medical personnel. Prevent aspiration of vomit. Seek medical attention immediately. Turn victim's head to one side. If unconscious, place in recovery position. Never give anything by mouth to an unconscious person.

Primary Routes of Entry: Eye and skin contact, breathing vapors.

SECTION 5: Fire-Fighting Measures

Flash Point: 163 °F (73°C)

Method Used: ASTM D3278

Flammable Limits (STP In Air)

LFL/UFL: Not Determined

Suitable Extinguishing Media: Water fog, alcohol-resistant foam, CO₂, and dry chemicals such as sand and powdered limestone

Unsuitable Extinguishing Media: None known

Specific Hazards and Procedures: Heated containers may burst. Ammonia gas may be liberated at high temperatures. Incomplete combustion may result in the formation of toxic nitrogen oxide compounds (NO_x) and carbon monoxide. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated. The material is toxic to aquatic life. Fire residues and water contaminated with this material must be contained and prevented from entering waterways, sewers or drains.

Hazardous Combustion Products: Burning material may generate ammonia gas and noxious and toxic fumes. Combustion and/or decomposition products include carbon monoxide and nitrogen oxides (NO_x).

SECTION 6: Accidental Release Measures

Personal Protective Measures: Provide adequate ventilation and keep all unnecessary and unprotected personnel from entering the area. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Wear an appropriate respirator when ventilation is inadequate. Use appropriate safety equipment before taking any action.

Methods and Material for Containment and Cleaning Up: Stop flow of material with sand or other inert material and move container from spill area. Absorb spill with an inert material, scrape up and place in appropriate waste disposal container. Remove residual resin with non-flammable solvent and flush contaminated area with hot water. Do not dump waste into any sewers, on the ground or into any body of water. Avoid dispersal of spilled material and runoff. All disposal methods must be compliant with all Federal, State, and local laws and regulations.

SECTION 7: Handling and Storage

Precautions for Safe Handling: Wear safety glasses. Do not combine this product with sodium nitrite or other nitrosating agents. Suspected cancer-causing nitrosamines could be formed. Avoid contact with acids, oxidizers, acrylates, alcohols, aldehydes, ketones and halogenated hydrocarbons. Avoid contact with metal such as copper, copper alloys, brass and bronze. Wear personal protection equipment including safety glasses. Do not get in eyes, on skin or on clothing. Avoid any forms of ingestion. Do not breathe vapor, mist or spray. Use only with good ventilation or use suitable respiratory protection. Persons with a history of skin sensitization problems should avoid contact with any process in which this product is used. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage, Including Any Incompatibilities: Store in tightly sealed, original container in a cool, dry and well-ventilated place protected from direct sunlight. Keep container sealed until use. Keep containers tightly closed when not in use. Store away from incompatible materials such as acids and food and drink. Use appropriate containment to avoid environmental contamination. Product may freeze with extended exposure to low temperatures. If this occurs, warm the product to 100 – 140°F (38 – 60°C) for one hour and stir until clear.

SECTION 8: Exposure Controls/Personal Protection

Occupational Exposure Limits for formulated product:

None available

Occupational Exposure Limits for individual components:

Chemical	CAS #	OSHA PEL 8-hr TWA	NIOSH REL 15 min. ceiling	NIOSH REL TWA	NIOSH IDLH	ACGIH TLV 8-hr TWA
phenol	108-95-2	5 ppm	15.6 ppm	5 ppm	250 ppm	5 ppm
m-phenylenebis(methylamine)	1477-55-0		0.1 mg/m ³			0.1 mg/m ³ (ceiling)
2-ethoxyethyl acetate	111-15-9	100 ppm		0.5 ppm	500 ppm	5 ppm

Engineering Controls: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If user operations generate vapor, process enclosures or local exhaust may be necessary.

Individual Protection Measures

Eye/Face Protection: Use properly fitted safety glasses. If vapor exposure causes eye discomfort, a full-face respirator may be necessary.

Skin Protection: Wear protective clothing suitable to the conditions of use. Clean, body-covering clothing and protective gloves should be worn at all times when handling the product.

Respiratory Protection: If local exhaust ventilation is inadequate, use a properly fitted, air-purifying mask suitable to the level of anticipated exposure.

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Wash contaminated clothing before reusing.

SECTION 9: Physical and Chemical Properties

Physical State: Clear amber liquid

Odor Threshold: Not determined

Melting Point/Freezing Point: Not Determined

Flash Point: 73 °C (163°F)

Flammability: Combustible

Vapor Pressure: Not determined

Relative Density (water = 1): 1.11-1.15@ 22°C

Partition Coefficient: Not determined

Decomposition Temperature: Not determined

Explosive Properties: None

Odor: Irritating, amine

pH: 9.5 – 10.5 (1% solution)

Boiling Point: Not Determined

Evaporation Rate: Not determined

Explosive Limits: Not applicable

Relative Vapor Density: Not applicable

Solubility: Slightly soluble in water

Auto-Ignition Temp.: Not determined

Viscosity: 300-900 cps

Oxidizing Properties: Slight

SECTION 10: Stability and Reactivity

Reactivity: Product reacts exothermically with epoxide resins. Product by itself is stable and relatively non-reactive under normal conditions of use, storage and shipping.

Chemical Stability: Product is stable under normal use and temperature conditions. Prolonged excessive heat may cause partial degradation.

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid: Avoid contact with incompatible materials. Avoid excessive heat. Store between 40-90° F.

Incompatible Materials: Avoid contact with acids, oxidizers, acrylates, alcohols, aldehydes, ketones and halogenated hydrocarbons. Avoid contact with metal such as copper, copper alloys, brass and bronze. Avoid bulk contact with epoxides. Material reacts with considerable heat release with some epoxide resins.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, acrid smoke and fumes

Hazardous Polymerization: Will not occur by itself, but hazardous polymerizations may occur with aliphatic amines combined with epoxides in masses greater than one pound with considerable heat buildup.

SECTION 11: Toxicological Information

Acute Toxicity:

Component	Oral LD 50	Dermal LD 50	Inhalation LC 50
Finished product (major component)	>2,200 mg/kg (rat)	>1,000 mg/kg (rabbit)	>20mg/L (rat)
m-phenylenebis(methylamine)	980 mg/kg (rat)	2000 mg/kg (rabbit)	1.34 mg/L (rat, 4 hr)
phenol	317 mg/kg (rat)	630 mg/kg (rabbit)	900 mg/m ³ (rat, 8 hr)
2-ethoxyethyl acetate	2,700 mg/kg (rat)	10,000 mg/kg (rabbit)	12,100 mg/m ³ (rat, 8 hr)

Skin Corrosion/Irritation: The formulated product is considered a severe skin irritant. Brief contact may cause skin burns.

Component	Species	Skin Exposure	Observation
m-phenylenebis(methylamine) (OECD Test Guideline 404)	Rabbit	>3 min - <1 hr	Corrosive
Phenol		>3 min - <1 hr	Corrosive

Serious Eye Damage/Irritation: The formulated product is considered a severe eye irritant. Exposure may cause severe irritation with corneal injury which may result in permanent impairment of vision.

Component	Species	Eye Exposure	Observation
Finished product (major component)			Severe Irritant
Phenol	Rabbit	100 mg, 24 hours	Severe Irritant

Respiratory or Skin Sensitization: Sensitization is possible through skin contact. Sensitization has occurred in lab animals after repeated exposures.

Germ Cell Mutagenicity: No data for the product itself.

Component	Test	Species	Result
m-phenylenebis(methylamine)	Ames	S. typhimurium	Negative
m-phenylenebis(methylamine)	Micronuclear	mouse	Negative

Carcinogenicity: No components of this product are listed or classified as carcinogens by IARC, NTP, OSHA or ACGIH.

Reproductive Toxicity: Not available

STOT-Single Exposure: Not Available

STOT-Repeat Exposure: Not Available

Routes of Exposure: Skin contact, eye contact, vapor inhalation.

Primary Symptoms: Material is a severe eye and skin irritant and moderate skin sensitizer. Prolonged exposure can cause dryness and cracking of the skin. Material vapor can be irritating to the respiratory and digestive tracts, and may be harmful if swallowed or inhaled in large amounts.

Effects of Overexposure: Overexposure to vapors can cause dizziness, headaches and other central nervous system effects.

SECTION 12: Ecological Information

Acute (short-term) toxicity: The formulated product is toxic to aquatic organisms on an acute basis.

Component: m-phenylenebis(methylamine) (following OECD Test Guidelines 203, 202 and 201 as appropriate)

Species	Result	Exposure
Oryzias latipes	LC50: 97.6 mg/L	96 hour; semi-static
Daphnia magna (water flea)	EC50: 15.2 mg/L	48 hour; static
Pseudokirchneriella subcapitata (green algae)	EC50: 32.1 mg/L	72 hour; growth rate inhibition
Bacteria (aerobic sludge treatment)	EC50: >1000 mg/L	Respiration inhibition

Chronic (long-term) toxicity: The formulated product may cause long-term effects in the aquatic environment.

Persistence and Degradability: No information for the product itself.

The major component, m-phenylenebis(methylamine), is not readily biodegradable, 49% in 28 days. (OECD Test Guideline 301B)

Bioaccumulative potential: Partition coefficient n-octanol /water (log Pow): Not Available

Mobility in soil: Not Available

SECTION 13: Disposal Considerations

Disposal considerations apply only to the product as shipped in its original container.

Waste Disposal: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer. The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transportation Information

US DOT:

UN Number:	2735
UN Proper Shipping Name	Amines, liquid, corrosive, n.o.s. (Benzene-1,3 dimethaneamine)
Hazard Class:	8
Packing Group:	II
Marine Pollutant:	Not Applicable

In quantities not over 1 L or 1 Kg this product can be shipped as a limited quantity.

SECTION 15: Regulatory Information

HCS Classification: Irritating material, Sensitizing material

TSCA Status: All materials are either included on or exempt from the TSCA Inventory of Chemical Substances. This product does not contain any components subject to TSCA 12(b) export notification.

Global Chemical Inventory Status: All materials are either listed, compliant with or exempt from listing on the following global inventories:

Country/Region	Inventory Name	Listed?
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
EU	European List of Existing Commercial Chemical Substances (EINECS)	Yes
EU	European List on Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory of Chemicals (NZIoC)	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
USA	Toxic Substances Control Act Inventory (TSCA)	Yes

SARA 313 Components

This material contains 2-ethoxyethyl acetate (listed as glycol ethers) (CAS# 111-15-9) which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

Other Regulations: This product contains no Extremely Hazardous Substances, EPCRA Sec.311, Appendix A and B.

California Proposition 65: This product does not contain any chemicals known to the State of California to cause cancer or reproductive or developmental effects.

SECTION 16: Other Information

HMIS Rating: The Hazardous Materials Identification System (HMIS) is a rating system with 0 representing a minimal risk or hazard and 4 representing a significant risk or hazard.

Health	3
Flammability	1
Physical Hazard	0

SDS History:

Version:	1
Revision Date:	October 25, 2021
Previous Update:	N/A
Creation Date:	October 28, 2020
Revision Notes:	N/A

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED, IS MADE.